HAULER® 800X

NO TASK IS OFF LIMITS.

Every part of the Hauler 800X is designed to go the extra mile, then go 50 more. Complete with an 8.4 cubic-foot cargo bed, bench seating, lifted suspension, and improved surface tires, the Hauler 800X approaches every job with the perfect mix of toughness and real-world utility. Available with your choice of a fuel-efficient 13.5 hp EFI gas engine or an ELiTE® lithium powertrain activated by Samsung SDI battery technology.

ELiTE® LITHIUM

8.4 CU FT
CARGO BED

500 LB
TOWING CAPACITY

725 LB
VEHICLE LOAD CAPACITY

HIGHER
GROUND CLEARANCE

ZERO MAINTENANCE
ELiTE LITHIUM BATTERY

HAULER 800X

ELiTE LITHIUM POWERTRAIN

- Zero Maintenance Battery
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Multifunction SOC/Speedometer Gauge
- Automatic Park Brake
- Limited Slip Differential

OPTIONS & ACCESSORIES

- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights
- LED Taillights/Brake Lights
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Rear Receiver Hitch
- Hour Meter
- Limited Slip Differential
- Rapid On-Board Charger
- Fuel/Oil Gauge

CUSHMAN.COM

	HAULER 800X ELiTE	HAULER 800X GAS
BODY & CHASSIS		
FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	110 in (279.4 cm)	
OVERALL WIDTH	49 in (125 cm)	
OVERALL HEIGHT	51 in (129.5 cm) (w/o Roof) / 74 in (188 cm) (w/ Canopy)	
WHEEL BASE	65.5 in (166.4 cm)	
WHEEL TRACK	37 in (94 cm) Front / 38 in (96.5 cm) Rear	
GROUND CLEARANCE	5.5 in (14.0 cm)	
CARGO BOX CAPACITY	8.4 cu ft (0.24 cu m)	
CARGO BOX DIMENSIONS	28.5 in (L) x 44.5 in (W) x 12 in (D) (72.4 cm x 113 cm x 30.5 cm)	
CARGO BOX MATERIAL	Roto-Molded Polyethylene	
POWER		
POWER TRAIN	56.7V Li-Ion Battery	4-Cycle, 24.5 cu in (401cc)
VALVE TRAIN	N/A	Single Cylinder OHV
HORSEPOWER (KW)	11.7 hp (8.7 kW) Peak	13.5 hp (10.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary	Starter/Generator. Solid State Reg.
BATTERY (QTY/TYPE)	2.2 Elite - Single Pack	One, 12V Maintenance Free
KEY OR PEDAL START	Pedal	
AIR CLEANER	N/A	Replaceable Industrial Rated Dry Cartridge
LUBRICATION	N/A	Pressurized Oil System
OIL FILTER	N/A	Spin-On
COOLING SYSTEM	N/A	Air Cooled
FUEL CAPACITY	N/A	5.96 Gallon (22.6 L) tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission
TRANSAXLE	Differential w/ Helical Gears	
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse / Key Switch	Forward - Reverse
REAR AXLE RATIO	16.99:1	11.47: 1 (Forward) 14.35:1 (Reverse)
PERFORMANCE		
SEATING CAPACITY	2-Person (Bench)	
WEIGHT W/O BATTERIES	744 lb (351 kg)	800 lb (362.9 kg)
CURB WEIGHT	821 lb (372 kg)	830 lb (376 kg)
VEHICLE LOAD CAPACITY	725 lb (328.9 kg)	
BED LOAD CAPACITY	325 lb (147.4 kg)	
TOWING CAPACITY	500 lb (226.8 kg)	
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
SPEED	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-Adjusting Drum	
PARKING BRAKE	Automatic Electro-Magnetic	Self-Compensating, Single-Point Engagement
TIRES (FRONT & REAR)	20 x 8-10 (6 Ply Tires)	

Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model. California state law prohibits the sale of Model Year 2025 and later gas-powered carts. ©2024 Textron Specialized Vehicles Inc. 82291-G12 (Rev. 06/2024)

CUSHMAN