Pro XD Full-Size Diesel Crew

Key Specifications

Diesel	1,950	200-Hr
Fuel Type	lbs Payload	Maintenance Interval

ANSI/OPEI Certification

Polaris Industries Inc. certifies that these vehicles complies with the American National Standard for Multipurpose off-Highway Utility Vehicles, ANSI/OPEI B71.9 – 2016 Standard

Engine & Drivetrain

Air Intake	Front Air Intake with Donaldson® Cyclonic Air Filter
Cooling	Liquid
Cylinders Displacement	898 cc
Drive System Type	On-Demand 4x4
Engine Type	3-Cylinder Kubota® Diesel
Fuel System/Battery	Mechanical Injection
Horsepower	24.5 HP
Maintenance Interval	200 Hours (50 Hour initial)
Top Speed	26 mph (41 km/h) *Adjustable with accessories
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

Dimensions

Bed Box Dimensions (L x W x H)	43.5 x 54 x 11.5 in (110.5 x 137 x 29 cm)
Box Capacity	1,250 lb (567 kg)
Estimated Dry Weight	1,878 lb (852 kg)
Fuel Capacity	11.5 gal (43.5 L)
Ground Clearance	11 in (27.9 cm)
GVWR	4,000 lb (1,814 kg)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising.

Manage Settings Accept Decline All

Person Capacity	4
Turning Radius	207 in (525 cm)
Wheelbase	117 in (297.2 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
Parking Brake	Park in Transmission + Separate Mechanical Parking Brake Standard

Additional Specifications

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride®
Hitch Type	Standard 2 in (5 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Engine Temperature, Hi-Temp Light, Clock, Clutch Belt Slip Warning, Glow Plug Indicator, Low Oil Pressure Indicator, Seat Belt Indicator, Parking Brake Engaged Alarm
Lighting	55W low/ 60W high, LED Tail
Other Standard Features	Horn, Backup Alarm, Mechanically Controlled Speed Limiting
Seat Covering	Kevlar®-Backed Vinyl (Grey)
Tilt Steering	Standard

Tires / Wheels

Electronic Power Steering	Standard
Front Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Hubs	Front: Steel; Rear: Ductile Iron
Rear Tires	26 x 10-12 Duro® DI-2042 Power Grip (M/T)
Wheels	12 x 6 HD Steel - Gloss Black

Suspension

Front Suspension	9 in (22.9 cm)
Rear Suspension	9 in (22.9 cm)

This site uses cookies and related technologies, as described in our privacy policy, for purposes that may include site operation, analytics, enhanced user experience, or advertising.